

### **Thermablok**™

Revision Date: 07Jan2009

## 1. IDENTIFICATION OF THE SUBSTANCE AND OF THE COMPANY

**Product Name:**Synonyms:
Thermablok Thermal Acoustic Isolation Strips
Silica gel, trimethylsilylated; silica aerogel materials

**Use of the Substance/Preparation:** High performance insulation material

Manufacturer: Acoustiblok, Inc.
Address: 6900 Interbay Blvd.
Tampa, FL 33616 USA

**Telephone:** 813-980-1400 **Emergency Telephone Number:** 813-980-1400

### 2.HAZARDS IDENTIFICATION

**Appearance and** White fabric material with no characteristic odor. Under certain conditions,

**Odor:** product may have faint ammonia-like odor. Shrink wrap packaged to minimize dust.

**Emergency** Inhalation of excessive amounts of dust from the product may cause mechanical irritation

**Overview:** to the respiratory tract. Dermal contact may cause mechanical irritation.

#### POTENTIAL HEALTH EFFECTS

**Inhalation:** Inhalation of airborne dusts may cause mechanical irritation of the upper respiratory tract.

Eye Contact: Exposure to dust from this product can produce a drying sensation and mechanical irritation of the

eyes.

**Skin Contact:** Skin contact with dust from this product can produce a drying sensation and mechanical Irritation of

the skin and mucous membranes.

**Ingestion:** This material is not intended to be ingested (eaten). If ingested in large quantity, the material may

produce mechanical irritation and blockage

**Acute Health** Dust from this product is a physical irritant, and may cause temporary irritation or scratchiness

**Hazards:** of the throat and / or itching and redness of the eyes and skin.

Chronic Health Some studies of long term amorphous silica dust exposures indicate a potential for decreased

**Hazards:** lung function. In surveyed studies, this effect is characterized as compounded by smoking.

Additionally, surveyed studies characterize the decreased lung function effect as reversible on

discontinuation of exposure.

Per the fiberglass manufacturer, the fiberglass is considered textile grade and is not classified as a

human carcinogenic by IARC (Group 3), ACGIH (Group A4), NTP, or OSHA.

**Medical** Excessive inhalation of dust may aggravate pre-existing chronic lung conditions **Conditions** including, but not limited to, bronchitis, emphysema, and asthma. Dermal contact

Aggravated by may aggravate existing dermatitis.

Exposure:

#### CARCINOGENICITY

·			
Component	ACGIH	NTP	IARC
Continuous Filament Glass Fibers	A4	Not Listed	3
Amorphous Silica	NA	Not Listed	None

**SECTION 2 NOTES:** This product is composed of synthetic amorphous silica dioxide, often referred to as silica gel or amorphous precipitated silica. Amorphous silica should not to be confused with crystalline silica. Epidemiological studies indicate low potential for adverse health effects from exposure to amorphous silica.



## Thermablok™

Revision Date: 07Jan2009

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient	CAS Number	Percent	EINECS #	EU Classification
Silica gel, trimethylsilylated	126877-03-0	30-50	Not Assigned	None
Polyethylene terephthalate (PET or polyester)	25038-59-9	25-35	Not Assigned	None
Fibrous glass (textile grade)	NA	25-35	Not Assigned	None

### 4. FIRST AID MEASURES

**Eye Contact:** Immediately wash with large amounts of water for at least 15 minutes, occasionally lifting lids.

If irritation occurs and persists, get medical treatment.

Skin Contact: Wash skin thoroughly with soap and plenty of water. Remove contaminated clothing and

shoes. Wash clothing before reuse. Obtain medical attention if symptoms occur.

**Ingestion:** Material will pass through the body normally.

**Inhalation:** Remove to fresh air. Drink water to clear throat and blow nose to remove dust.

Obtain medical attention if ill effects persist.

### 5. FIRE-FIGHTING MEASURES

#### **5.1 FLAMMABILITY PROPERTIES**

Auto ignition Temperature

Flash Point

Flammability Limits: (Lower Explosive Limit)

Flammability Limits: (Upper Explosive Limit)

Not Applicable

Not Applicable

Not Applicable

#### **5.2 EXTINGUISHING MEDIA:**

Use media suitable for surrounding fire and that are appropriate to the surrounding environment; normal fog nozzle water application and/or exclusion of air is typically suitable for extinguishing this product..

### **5.3 PROTECTION FOR FIRE FIGHTERS**

**Special Fire Fighting** Normal fire fighting procedures should be followed to avoid inhalation of smoke and

**Procedures:** gases produced by a fire.

**Unusual Fire and**Product is a super-insulation material. Densily packaged or stored material may retain heat within the internal layers causing re-ignition in the presence of oxygen if heat is not removed

**Hazardous Decomposition** Primary combustion products are carbon monoxide and carbon dioxide.

**Products:** 

### 6. ACCIDENTAL RELEASE MEASURES

**Personal Precautions:** Minimize dust generation. Ensure adequate ventilation. Use personal protective

equipment as necessary.

**Environmental Precautions:** Material is not soluble. Do not flush into surface water or sanitary sewer system.

Methods for Cleaning Up: Contain and collect released material for proper disposal. Dry vacuum is the

preferred method of cleaning up.



Thermablok™

Revision Date: 07Jan2009

# 7. HANDLING AND STORAGE

**Handling** Thermablok will generate dust when handled or cut. Workplace exposure to all dusts should be

controlled with standard industrial hygiene practices. Local exhaust ventilation should be the primary dust control method. Dust released during the handling of Thermablok should be cleaned up promptly. Dry vacuuming is the preferred method for cleaning up dust. Sweeping is not an effective method of picking up aerogel dust. Because aerogel dust is hydrophobic, water is not effective as a

dust control agent.

**Storage** Thermablok should be kept in their packaging until they are ready to be used. Unpack the material in

the work area. This will help to minimize the area where dust exposure may occur. Trimmed material

and scrap should be promptly packed in disposal bags.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1 Exposure Limit Values

There are no exposure limits identified for the main product component, classified as synthetic amorphous silica. Exposure limits for synthetic amorphous silica are based on silica (CAS No. 7631-86-9).

CAS Number	Component Name	Exposure Limits	
7631-86-9	Silica, Amorphous	Germany TRGS 900	4 mg/m₃ (inhalable fraction)
		UK WFI	6 mg/m <sub>3</sub> (total inhalable

fraction)

2.4 mg/m<sub>3</sub> (respirable fraction)

US OSHA PEL (TWA)a 15 mg/m3 (total dust)

5 mg/m<sub>3</sub> (respirable fraction)

5 mg/m<sub>3</sub> (respirable fraction)

US ACGIH<sub>b</sub> 10 mg/m<sub>3</sub> (inhalable)

3 mg/m<sub>3</sub> (respirable)

Continuous filament US ACGIH 1.0 fibers/ccc

5 mg/m³ (inhalable)

US OSHA 10 mg/m<sub>3</sub> (total dust)

<sup>a</sup> The US OSHA standard for amorphous silica is: (80 mg/m<sub>3</sub>)/(%SiO2). The NIOSH Sampling Method 7501 for Amorphous Silica calculates the %SiO2 based on the percentage of crystalline silica in the sample. Because the percentage of crystalline silica in aerogel is 0%, the particulate limit

glass fibers

#### **8.2 Exposure Control**

NA

**Ventilation:** Local exhaust in accordance with general industrial hygiene practices is recommended to

control dust.

**Respiratory**A properly fitted, NIOSH or CE approved respirator should be worn when ventilation is unavailable or inadequate to maintain airborne concentrations below applicable

is unavailable or inadequate to maintain airborne concentrations below applicable occupational exposure limits. A respiratory protection program that meets applicable local regulations should be implemented whenever workplace conditions warrant use

of a respirator.

Hand Protection Silica aerogels are hydrophobic (repel water) and may cause drying and irritation of

the skin, eyes, and mucous membranes. For this reason, nitrile, latex, or other

impermeable gloves should be worn when handling aerogel blankets.

**Eye Protection:** Safety glasses, or chemical goggles as needed to provide greater protection from dust.

b US ACGIH based on Particles Not Otherwise Specified (PNOS)

c Respirable fibers: length >5 µm; aspect ratio ≥3:1, as determined by the membrane filter method at 400–450X magnification (4-mm objective), using phase-contrast illumination. US NIOSlengthµm, width <3 µm diameter and length:width ratios ≥3.



Thermablok™

Revision Date: 07Jan2009

**Skin Protection:** Long-sleeved, long-legged work clothes are also advised. Disposable coveralls

should be considered to minimize skin exposure and track out of aerogel dusts into

adjacent areas.

**Work Hygienic Practices:** Keep materials packaged until just prior to use. Die cut in preference to rotary or other cutting methods. Dry vacuum with proper filtration preferred to sweeping. Wash thoroughly after using the product. Wash clothing if dusty conditions present. Wash hands before eating or drinking.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

**Appearance:** White fabric blanket. Heat shrink packaged.

**Odor:** No characteristic odor. Under certain conditions, product may have faint ammonia-

like odor.

:Ha Not applicable. **Boling Point/Range:** Not applicable. **Flash Point:** Not applicable. Flammability (solid, gas): Not applicable. **Explosive Properties:** Not applicable. **Oxidizing Properties:** Not applicable. **Vapor Pressure:** Not applicable. Solubility: Insoluble. Viscosity: Not applicable. **Evaporation Rate:** Not applicable

### 10. STABILITY AND REACTIVITY

Chemical Stability: Stable

**Conditions to Avoid:** Prolonged exposure to temperatures above the recommended use temperatures.

Materials to Avoid: None known

**Hazardous** Under recommended usage conditions, hazardous decomposition products

**Decomposition Products** are not expected.

### 11. TOXICOLOGICAL INFORMATION

### **ACUTE TOXICITY**

Dust may cause mechanical irritation and dryness to eyes and skin.

### **Synthetic Amorphous Silica**

**Oral LD50:** >5,000 mg/kg **Inhalation LC50:** >2,000 mg/m<sub>3</sub> **Dermal LD50:** >3,000 mg/kg

**Eye Irritation:** Synthetic amorphous silica and silicates are not irritating to skin and eyes under experimental conditions, but may produce dryness following prolonged and repeated exposure. **Skin Irritation:** Synthetic amorphous silica and silicates are not irritating to skin and eyes under experimental conditions, but may produce dryness following prolonged and repeated exposure.

#### **CHRONIC TOXICITY**

Some studies of long term amorphous silica dust exposures indicate a potential for decreased lung function. In surveyed studies, this effect is characterized as compounded by smoking. Additionally, surveyed studies characterize the decreased lung function effect as reversible on discontinuation of exposure.



Thermablok™

Revision Date: 07Jan2009

#### **CARCINOGENICITY**

The International Agency for Research on Cancer (IARC) considers synthetic amorphous silica to be not classifiable as to its carcinogenicity to humans (Group 3). According to the manufacturer, the fiberglass in this product is considered textile grade fibrous glass and it is not classified as a carcinogen by ACGIH, IARC, NTP or OSHA.

**NOTE TO SECTION 11:** Toxicological information is based on literature review for synthetic amorphous silica (CAS No. 7631-86-9)

### 12. ECOLOGICAL INFORMATION

### **Aquatic Toxicity**

Synthetic Amorphous Silica Fish: LC50 > 10,000 mg/L (Brachydanio rerio: 96 hour), Method OECD 203

Daphnia magna: EC50 > 10,000 mg/l (24 hours), Method OECD 202

**Mobility** None expected due to insoluble nature of product.

**Persistence and Biodegradability** Not applicable for inorganic material.

Bioaccumulative Potential None expected due to insoluble nature of product.

Other Adverse Effects None expected.

**NOTE TO SECTION 12:** Ecological information is based on literature review for synthetic amorphous silica (CAS No. 7631-86-9)

### 13. DISPOSAL CONSIDERATIONS

Dispose in an approved landfill in accordance with federal, state / provincial, and local regulation. Cover promptly to avoid dust generation. This product is not regulated as a hazardous waste under US RCRA regulations.

### 14. TRANSPORT INFORMATION

Shipping Name: Not regulated for transport

Hazard Class:
UN Number:
Packing Group:
Required Label(s):
Marine Pollutant:
Additional Information
None

### 15. REGULATORY INFORMATION

### **EC REGULATORY INFORMATION**

Product is not a classified as a dangerous material or preparation as defined in EC Directives 67/548/EEC or 1999/45/EC.

#### **U.S. FEDERAL REGULATIONS**

**CERCLA (Comprehensive Response Compensation and Liability Act):** Product is not classified as hazardous or reportable under this requirement.

**SARA TITLE III (Superfund Amendments and Reauthorization Act):** Product is not classified as hazardous or reportable under this requirement.

**311/312 HAZARD CATEGORIES:** Materials in this product are classified as hazardous or reportable under this requirement.



## Thermablok™

Revision Date: 07Jan2009

**313 REPORTABLE INGREDIENTS:** Materials in this product are classified as hazardous or reportable under this requirement.

**STATE REGULATIONS:** Materials in this product appear on the following state hazardous substance lists: CA, IN, KY, MA, MN, NC, NJ, OR, PA. Check individual state requirements

**INTERNATIONAL REGULATIONS** Amorphous silica (CAS No. 7631-86-9), are listed on the WHMIS Ingredient Disclosure List at a concentration threshold of 1%.

**TSCA:** All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

# **16. OTHER INFORMATION**

NFPA HAZARD CLASSIFICATION		HMIS HAZARD CLASSIFICATION		
Health	1	Health	1	
Flammability	1	Flammability	1	
Reactivity	0	Reactivity	0	
Other	NA	Protection	Refer to Section 8	

#### **ABBREVIATIONS:**

**NA** Denotes no applicable information found or available.

**CAS Number** Chemical Abstract Service Number

**EINECS Number** European INventory of Existing Chemical Substances

**ACGIH** American Conference of Governmental Industrial Hygienists

**US OSHA** United States Occupational Safety and Health Administration

TLV Threshold Limit Value

**PEL** Permissible Exposure Limit

TWA Time-weighted average

IARC International Agency for Research on Cancer

**EU** European Union

NTP National Toxicology Program

R Risk

S Safety

LC50 Lethal Concentration 50%

LD50 Lethal Dose 50%

**NFPA** National Fire Protection Association

HMIS Hazardous Materials Identification System

**US DOT** United States Department of Transportation

**TDG** Transportation of Dangerous Goods Regulation

Section 11 Synthetic Amorphous Silica Toxicity Information Reference: United Nations Environmental Programme (UNEP), Organization for Economic Co-operation and Development (OECD) Screening Information Data Set (SIDS) Initial Assessment Report, Synthetic Amorphous Silica, July 23, 2004.

Revision Summary: The revised safety data sheet replaces all previous versions. The safety data sheet was modified to update format and clarify content.

**DISCLAIMER:** The information herein is presented in good faith and believed to be accurate as the effective data given. However, no warranty, expressed or implied, is given. It is the user's responsibility to ensure that its activities comply with Federal, State or Provincial, and local laws.